

Isetta

Promotional ice-cream cabinets with static refrigeration, finned evaporator and automatic electric defrosting. One piece body with ecological polyurethane insulation (HCFC & HFC free), foamed with CO₂. Internal and external tank in plastified sheet. This cabinet can be fitted with a double level of ice-cream containers H120 and it is equipped with a storage cell with internal foamed evaporator (except for the model ISETTA 4). Tempered glass structure, available in two versions, ST (straight front glass) or LX (curved front glass). Rear pivoting methacrylate panel system on operator side. Work top in plastified sheet with internal led lighting. Built-in hermetic condensing unit with electronic control board. Available in Special Performance TP model working in class 7, 35°C, 75 RH. Main structure in carbon steel painted with powder, 4 pivoting wheels for an easier handling.

Vetrine gelato promozionali a refrigerazione statica con evaporatore alettato e sbrinamento automatico elettrico. Scocca monolitica coibentata con poliuretano ecologico (HCFC & HFC free) espanso a CO₂. Interno ed esterno vasca in lamiera preverniciata. La vetrina può contenere un doppio livello di vaschette H120 ed è dotata di cella di riserva a refrigerazione statica con evaporatore a mantello (eccetto il modello ISETTA 4). Sovrastruttura in vetro temperato, disponibile nelle due versioni, ST (vetro frontale dritto) o LX (vetro frontale curvo). Chiusura lato operatore tramite ribaltina basculante in metacrilato. Piano di lavoro in lamiera plastificata, con plafoniera di illuminazione con led sul lato interno vasca. Unità condensatrice ermetica a bordo con quadro comandi elettronico. Versione TP tropicalizzata [classe 7, 35°C; 75% UR]. Struttura in acciaio al carbonio verniciato a polvere, con 4 ruote pivotanti per facilitarne la movimentazione.



ENERGY SAVING
Led



INSTALLATION
Plug-in



TEMPERATURE
-16/-14 °C



DEFROST
Electric



CLIMATIC CLASS
7





Isetta Catalog - Catalogo

Model Modello			Code Codice		Condensing unit included Unità condensatrice a bordo	
			R404A	R290	R404A Air / Aria	R290 Air / Aria
RS	ST TP	4	-	-	*****	*****
		6R	-	-	*****	-
		7R	-	-	*****	*****
RS	LX TP	4	-	-	*****	*****
		6R	-	-	*****	-
		7R	-	-	*****	*****
		9R	-	-	*****	-
		12R	-	-	*****	-

Isetta Technical features - Caratteristiche tecniche

	4		6R		7R	
External dimensions (LxDxH) Dimensioni esterne [LxPxH]	824 x 760 x 1176 mm		1184 x 800 x 1176 mm		1354 x 800 x 1176 mm	
Storage containers capacity Capacità vaschette di riserva	-		4 [+4] / 5 lt - 6 / 4,75 lt		6 [+6] / 5 lt - 8 / 4,75 lt	
Net weight Peso netto	69 kg		97 kg		102 kg	
Refrigeration Refrigerazione	Static - Statica					
Refrigerant Refrigerante	R404A ^[1] - R290 ^[2]					
Climatic class Classe climatica	7					
Operating conditions Condizioni ambientali	35 °C / 75 %RH					
Product temperature Temperatura prodotto	-16/-14 °C					
Compressor [q.ty-type] Compressore [q.tà-tipologia]	1 Hermetic - 1 Ermetico					
Defrost Sbrinamento	Electrical - Elettrico					
Power supply Alimentazione	230 V / 1 Ph / 50 Hz					
Electrical input [standard] Assorbimento elettrico [standard]	^[1] 330 W / 2,3 A	^[2] 300 W / 2,4 A	^[1] 590 W / 4,1 A	^[1] 870 W / 5,8 A	^[2] 500 W / 2,6 A	
Electrical input [defrost] Assorbimento elettrico [sbrinamento]	^[1] 810 W / 3,8 A	^[2] 810 W / 3,8 A	^[1] 810 W / 3,7 A	^[1] 915 W / 4 A	^[2] 915 W / 4 A	

Stainless steel containers

Vaschette inox



Piled up double row

Doppia fila di riserva

5 Lt

360 x 165 x 120h

9001990000005

***** each/cad.



4,75 Lt


260 x 157 x 170h

9001990000003


***** each/cad.

Section - Sezioni


ST 4




ST 6R-7R



LX 4



LX 6R-7R-9R-12R



9R	12R
1659 x 800 x 1176 mm	2119 x 800 x 1176 mm
7 [+7] / 5 lt - 10 / 4,75 lt	10 [+10] / 5 lt - 14 / 4,75 lt
160 kg	217 kg
Static - Statica	
R404A [1] - R290 [2]	
7	
35 °C / 75 %RH	
-16/-14 °C	
1 Hermetic - 1 Ermetico	2 Hermetic - 2 Ermetico
Electrical - Elettrico	
230 V / 1 Ph / 50 Hz	
[1] 930 W / 5,5 A	[1] 1045 W / 5,6 A
[1] 1330 W / 5,8 A	[1] 1755 W / 8,2 A

***** See price list / Vedi listino prezzi

Isetta **Customizable area** - Aree personalizzabili

